#### **VANDAL RESISTANT**



#### **INTERCOM ASSEMBLY**

2-Gang Call-In Station, Vandal Resistant, Stainless Steel

#### **GENERAL DESCRIPTION**

The CIS4 Series is a 2-gang, vandal resistant call-in station with integrated speaker/microphone consisting of a 2.5" square frame loudspeaker with a 2.35 oz. ceramic magnet and a phenolic impregnated, moisture resistant cone a 1W-25V transformer, and a momentary (normally open) push-to-call button.

Three (3) interwoven, steel security screens are mounted between the 12 guage brushed stainless steel faceplate and loudspeaker. Tamper resistant, 6-32 x 1" 'pin-in-torx' hardware included.

### **MODELS AVAILABLE**

CIS4/8 8 Ohm Speaker

CIS4/25 1W-25V, 3-Tap Transformer (1W, 0.5W, 0.25W)

CIS4/45 | 45 Ohm Speaker

# **INTENDED USE** - Indoor or Protected Outdoor Environment

Program Material | Signal Tones and Voice

## **AUDIO SPECIFICATIONS**


Average Sensitivity Frequency Response Nominal Coverage Angle Audio Connection


87 dB SPL, 1W/1M Magnet Type & Weight | BeFe Ceramic, 2.35 oz. Nominal 200 Hz - 8 kHz EIA 426A Standard 90° Included Angle, -6 dB / 2 kHz, Half space 25V: 7" Color-Coded Leads, Pre-Cut 8 & 45 Ohm: 0.205' Spade Terminal

# RECOMMENDED QUAM COMPONENTS

**Enclosures** | Surface Mount : SE7GVP, SE8GVP, SE9GVP







Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the Specs and Diagrams section at: www.QuamSpeakers.com





