

## Dual Temp and Humidity Sensors (THS00 / THS01)



Accurate and responsive measurement of temperature and humidity. Available in fixed length or extendable version, the sensor is housed in a metal tube that is thermally conductive and perforated to still provide accurate readings.



### THS00

The THS00 is supplied with a free 5ft cable, it can be extended using standard CAT5 up to 300 meters (1,000ft) from the AKCP base unit. The sensor can be mounted with screws, adhesive or with optional DIN rail clips



### THS01

A short 1ft fixed cable with a dual temperature and humidity sensor on the end. Custom lengths can be ordered to suit your needs. Product code for custom lengths is THSxx where xx is replaced by the cable length in feet.\*

\*Water resistant version can be ordered on request, product code is THSWxx, where xx is the length of fixed cable in feet.

## Dual Temp and Humidity Sensors (THSxx-NIST2 / NIST4)



# If you're spending money for monitoring, wouldn't you want to know the sensors are calibrated?

## **2 NIST certified, calibrated temperature sensors are compared once a second for accuracy. (NIST2)**

The NIST2 sensors feature a built in calibration check. Each unit has 2x NIST calibrated and certified temperature sensors. The primary sensor value is checked by the secondary sensor, and if we detect a range of greater than the stated accuracy we will alert that the sensor is out of calibration.

This makes these sensors ideal for situations where a high degree of accuracy is required and assurance of the calibration state

## **Calibration Check with Fail-over**

## **2 NIST certified, calibrated temperature sensors are compared once a second for accuracy, with a second backup pair (NIST4).**

The NIST4 sensors feature a built in calibration check. Each unit has two pairs of NIST calibrated and certified temperature sensors. The primary sensor value is checked by the secondary sensor, and if we detect a range of greater than the stated accuracy we will alert that the sensor is out of calibration. The sensor will then automatically fail-over to the second pair and continue monitoring with a seamless graph of data.

Suitable for situations where a high accuracy, calibrated sensors are needed, with backup for critical monitoring applications.

### THS00 / THS01 / NIST2 / NIST3 - Technical Specifications



<b>Temperature</b>	
<b>Measurement Range</b>	-55°C to +75°C -67°F to +167°F
<b>Measurement Resolution</b>	sensorProbe+ series 0.1°C increments 0.2°F increments securityProbe series 0.5°C increments 0.9°F increments sensorProbe series 1°C increments 1°F increments
<b>Measurement Accuracy</b>	sensorProbe+ series and securityProbe series ±0.5°C accuracy from -10°C to +75°C ±0.9°F accuracy from +14°F to +167°F sensorProbe series ±1°C accuracy from -10°C to +75°C ±1°F accuracy from +14°F to +167°F
<b>Humidity</b>	
<b>Measurement range</b>	0 to 100% Relative humidity
<b>Resolution</b>	1%RH increments, 0.01%RH sensor reading
<b>Accuracy at</b>	At 25°C Min : ±2%RH Max : ±5% RH
<b>Interface</b>	
<b>Communications cable</b>	RJ-45 jack to sensor using UTP CAT5e/6 cable
<b>Power source</b>	Powered by the base units. No additional power needed
<b>Power Consumption</b>	Typical 17.25mWatt, 1.45mA
<b>Maximum Cable Length</b>	THS00 - SPX+ 1000 feet (300 meters) with approved low capacitance shielded UTP cable THS00 - SP2+ / SP1+ 600 feet (180 meters) with approved low capacitance shielded UTP cable THS01 - 100 feet (30 meters)
<b>Sensor type</b>	Semiconductor, microprocessor controlled
<b>Dimensions</b>	56 x 55 x 33.3 mm
<b>Mounting</b>	DIN rail mounting Screw mounting
<b>Sensor count</b>	2
<b>Sensor count (NIST2/NIST4)</b>	3
<b>Important Note</b>	The fixed one foot type or THS01 are not designed to be extended. If you need to extend these sensors then you need to use the THS00 (remote type). We also do not recommend you trying to connect any of our AKCP sensors including the temperature and dual temp humidity sensors though patch panels or using the RJ-45 couplers to extend them. Please see the temperature sensors product manual or FAQ in our knowledge base for more details regarding this.
<b>Compatibility</b>	THSxx-NIST2 and THSxx-NIST4 compatible with sensorProbe+ series only

THS00 / THS01 / NIST2 / NIST4 - Technical Drawing

